Solstice Pod



Solstice transforms ordinary meeting and learning spaces into more collaborative multi-user environments by placing content at the center of the meeting experience. With Solstice, any number of participants can easily share and control content from laptops and mobile devices to the in-room display. Meetings start faster, participants are more engaged, and information flows freely, improving meeting results, productivity, and ROI.

Key Capabilities



Easy to Use
From the first connection,
Solstice delivers an
intuitive user experience.



Unlimited Collaboration Everyone in the meeting can share and control content collaboratively.



Multi-Network
Secure collaboration for users on multiple networks via the Pod's separate network interface cards.



User and admin authentication, network encryption of Solstice traffic, and annual 3rd-party penetration testing.



Centralized Management
The Solstice Dashboard provides
centralized, one-to-many
management of every room in
the Solstice deployment.



Integration API
Integrate Solstice with 3rd
party systems using our
RESTful API.



Active Product Roadmap and Software Upgrade Path

Solstice has an active product roadmap which Mersive delivers via lightweight software updates to address new market requirements. Solstice updates provide customers that have current software maintenance with access to all the features and improvements made available after the initial purchase date.

Hardware and Technical Specs



- HDMI 1.4
- Stereo out, 8-channel 7.1 surround sound
- Gigabit Ethernet
- 2x USB 2.0

Dimensions	
Hardware Type	Compute Console
Size	126mm x 101mm x 25.8mm
Weight	0.65lbs
System Specification	าร
Processor	Qualcomm Snapdragon™ S805, Krait 450
Graphics Processor	Adreno™ 420
Internal Storage	3GB RAM, 16GB Flash Storage
Ethernet	RJ45 Gigabit
Wireless	Dual band, 802.11ac 2×2 MIMO
Output	HDMI 1.4 output with Audio, Stereo output (8-channel 7.1 surround sound)
Streaming Video Support	HD (1920×1080), SD (1280×720)
I/O	2x USB 2.0
Power	
Input	DC 12V @ 3A max
Efficiency Level	VI
Adaptor	Switching 100-240VAC, 50/60Hz, changeable plug type (international support)
Adaptor Region Support:	US, EU, AK, AUS
Testing and Certifica	ations
Safety	UL
Emissions Testing	FCC, CE (Home and Office Use)
Regional Certification Marks	USA, Canada, Europe, China, Australia/New Zealand, Singapore, Mexico
Accessibility	WCAG 2.0 AA Compliant. Full VPAT document available.

